

ViewSonic® PJ750 Projector

High Brightness. Ultra-Portable.



Bright, versatile and portable.

The ViewSonic PJ750 projector delivers exceptionally bright presentations. With 2,300 lumens, 1024x768 XGA resolution and high contrast, this projector delivers clear, crisp images, even in well-lit rooms. Easy to use, the **FULL-FEATURED** PJ750 offers zoom and digital keystone correction as well as **MULTIPLE COMPUTER AND VIDEO INPUTS AND OUTPUTS FOR GREATER FLEXIBILITY**. Whisper-mode will make the most out of your investment by extending the lamp life and reducing noise output to whisper quiet levels. With the PJ750 projector, you'll confidently present a positive image anytime, anywhere.

High brightness and versatility.

❖ Ideal for mobile professionals.

Packs 2,300 lumens in just 7.2 lbs. It's the bright choice for the mobile professional.

❖ Supports digital signals including HDTV.

Capable of displaying HDTV signals as well as other video and data sources.

❖ Ultimate flexibility with multiple RGB inputs.

Connect two computers simultaneously or add a video source for dynamic meetings.

❖ Easy set-up and auto tuning.

One-touch setup button for fast, easy sync and sharp focus.

❖ The perfect image in any setting.

Digital horizontal and vertical keystone correction, short focal length and zoom function ensure the perfect size image in any room.

❖ Whisper-mode extends lamp life.

Extend the life of your lamp up to 4,000 hours* and reduce noise output.

❖ Free industry-leading 24/7 customer support.†

Technical Support wherever, whenever, just in case.

❖ The best warranty in the business.

Covered by a three-year parts and labor limited warranty, first-year Express Exchange® and one-year lamp warranty. **

ViewSonic has the **best warranty** and **service support** in the business!



3-Year Parts and labor limited warranty

1-Year Free Express Exchange®

1-Year Limited lamp warranty**

And we offer free 24/7† technical support for the life of your Product, just in case.

Super bright



ViewSonic®
See the difference.®

ViewSonic® PJ750 Projector

High Brightness. Ultra-Portable.



PJ750 Distance Calculator

Image Size (Diagonal in inches)	Height (in inches)	Width (in inches)	Throw Distance (in inches)
24	14.45	19.19	42.73
48	28.91	38.38	81.47
72	43.37	57.58	120.2
96	57.83	76.77	158.94
120	72.29	95.97	197.68
144	86.75	115.16	236.41
168	101.21	134.36	275.15
192	115.67	153.55	313.88

Accuracy of the calculations are +/- 5%.
For additional calculations visit ViewSonic.com.

Optional Accessories

Hard carrying case w/cart function	PRJ-HCA-001
Spare lamp	PRJ-RLC-001
Ceiling/wall mount kit	PM-750
Express Exchange® service	EE-LB-02

PORTABLE HIGH-BRIGHTNESS PROJECTOR

LCD	Type Pixel Format Lens	0.9" Polysilicon (x3) stripe pixel TFT active matrix 1024 horizontal x 768 vertical Manual zoom/focus (1:1.3x)
DISPLAY	Size Throw Distance Lamp Brightness Contrast Ratio	30"-300" (measured diagonally) 3.9'-51.0' (1.2m-15.7m) 200W UHB compact, 4,000 hour rating* 2,300 lumens 350:1
AUDIO	Speakers Power	Stereo 1Wx2
INPUT SIGNAL	Video Sync Frequency	RGB analog, NTSC, PAL-M, PAL-N, SECAM, HDTV Separate and composite Fh: 15~91kHz; Fv: 56~120Hz
COMPATIBILITY	PC Mac ^{®††}	From VGA up to SXGA (scaled) Up to SXGA (may require Mac ^{®††} Adapter)
CONNECTOR	RGB Input RGB Output Composite Video Component Video S-Video Audio (In/Out) Control USB	15-pin, D-sub (x2) 15-pin, D-sub (x1) RCA (x1) RCA (x3) Mini-Din 4 pin (x1) In RCA (x1) and 3.5mm (x2); Out 3.5mm (x1) 15-pin D-sub (x1) USB upstream (x1) available through RS232 port
POWER	Voltage Frequency Consumption	100-120V AC/220-240V AC 50-60Hz (universal) 290W (typ)
USER CONTROLS	Basic Remote OnView® OSD	Standby on/off, menu (left, right, up, down), input, reset, mute, keystone, indicator (lamp, power, temp) Standby on/off, video, laser, blank, RGB, disk pad, auto, mouse, menu, position, menu select (left, right, up, down), keystone, reset, freeze, magnify (+, -, off), volume (up, down), mute, timer Brightness, contrast, V. position, H. position, H. phase, H. size, color balance (red), color balance (blue), aspect ratio, auto, RGB, keystone, blank, mirror, start up, volume, menu color, timer, language, auto off, sync on green, whisper-mode
OPERATING CONDITIONS	Temperature Humidity	32° F-95° F (0° C-35° C) 10%-85% (non-condensing)
DIMENSIONS (W x H x D)	Physical	11.7" x 3.0" x 9.0" 298mm x 76mm x 228mm
WEIGHT	Net Gross	7.2 lbs. (3.25 kgs) 16.5 lbs. (7.5 kgs)
REGULATIONS		UL, FCC-B, c-UL, CE, CB Report, TUV/GS, CB Report, GOST, NOM, CCC, PJB
OTHER		Mirror reverse image, upside down image, digital horizontal/vertical keystone correction, DDC 1/2B
WARRANTY		Three-year limited warranty on parts and labor, first-year Express Exchange® service, one-year warranty on lamp.**

ISO 9001



FM 40187

ISO 14001



EMS 40968

ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.



ViewSonic®
See the difference.™

ViewSonic Corporation • 381 Brea Canyon Road, Walnut, CA 91789
Phone (800) 888-8583 or (909) 444-8888 • In Canada (866) 262-1967 • Fax (909) 839-7922 • SalesInfo@ViewSonic.com • ViewSonic.com

*Running Whisper-mode exclusively can extend lamp life up to 4,000 hours. **Lamp warranty available in U.S. and Canada. Subject to terms and conditions, verification and approval. Third-year and 1-year limited lamp warranties apply only to PJ250, PJ350, PJ500, PJ501, PJ550, PJ750, and PJ1065 projectors purchased after May 1, 2002. Applies to manufacturers installed lamp only. All accessory lamps purchased separately are warranted for 90 days. †Excluding major U.S. holidays. †† Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs may vary by country. See your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2003 ViewSonic Corporation. All rights reserved. [10157-088-08/03] PJ750-3

For more product information, visit us on the web at ViewSonic.com

Specifications