

ViewSonic® PJ755D Projector

HIGH BRIGHTNESS DLP™ MULTIMEDIA PROJECTOR



Brilliant, life-like color for powerful video.

The ViewSonic PJ755D DLP multimedia projector delivers brilliant color, sharp graphics and outstanding video. With 2,700 lumens, 2000:1 contrast ratio and 1024x768 optimum resolution, you'll be impressed by this **RICH, PROJECTOR'S SATURATED COLOR AND INCREDIBLY SMOOTH VIDEO.**

With digital (DVI) and analog (VGA) inputs and support for HDTV signals you can deliver professional multimedia presentations

in the office or view stunning, life-like DVDs and videos at home. Unlock the power of the **ULTRA-**

BRIGHT, HIGH-PERFORMANCE PJ755D

in your home or office.

ViewSonic® has the **best warranty** and **service support** in the business!



3-Year Parts and labor limited warranty

1-Year Free Express Exchange®

1-Year Lamp warranty

And we offer free 24/7 technical support! for the life of your Product, just in case.

Stunning color and clarity.

◆ Bright in virtually any setting

Packs 2,700 lumens in just 7.5 lbs., the choice of professionals for high brightness.

◆ Supports HD signals including 720p and 1080i

Capable of displaying HD signals as well as other video and data sources.

◆ Easy set-up and auto tuning

One-touch setup button for fast, easy sync and sharp focus.



Easy-to-use fully functional wireless remote control included.

◆ OnView® controls plus ViewMatch® color for superior screen adjustability

◆ The perfect image in any setting

Digital keystone correction, short focal length and zoom function ensure the perfect size image in any room.

◆ Whisper-mode extends lamp life

Extend the life of your lamp up to 4,000 hours* and reduce noise output.

◆ Ultimate flexibility with multiple inputs

Rich connectivity with RGB, DVI, component video, composite video and S-video inputs and a monitor output.

◆ The best warranty in the business

Covered by a three-year parts and labor limited warranty, first-year Express Exchange® and one-year lamp warranty.**



Super bright

ViewSonic®

ViewSonic® PJ755D Projector

HIGH BRIGHTNESS DLP™ MULTIMEDIA PROJECTOR



1. Stand by/on
2. Menu
3. PC/video inputs, monitor pass through and RS-232
4. Kensington security port
5. Zoom and focus rings

XGA PORTABLE DLP PROJECTOR

	Type	0.7" XGA Digital Micromirror Device (DLP™)
	Pixel Format	1024x768 XGA (native resolution)
	Lens	Manual zoom/focus
	Zoom Factor	1.2
	Keystone	Vertical ± 16°, horizontal ± 5°
DISPLAY	Size	25–246" (Diagonal)
	Throw Distance	3.9'–32.8'
	Throw Ratio	2 ~ 2.4:1
	Lamp	250W, 1,500 hours**
	Brightness	2,700 lumens
	Contrast Ratio	2000:1
	Aspect Ratio	4:3 (native), 16:9
INPUT SIGNAL	Video	NTSC 4.43, PAL, SECAM, HDTV (480i, 480p, 576p, 720p, 1080i)
	Frequency	Fh: 15–100KHz; Fv: 43–120Hz
COMPATIBILITY	PC	Analog: from VGA up to UXGA (scaled)
	Mac††	Analog: up to SXGA
CONNECTOR	RGB (input)	DB-15 (x1)
	DVI (input)	DVI (x1)
	RGB (output)	DB-15 (x1)
	Component Video (input)	RCA jack (x1 set)
	Composite Video (input)	RCA jack (x1)
	S-Video (input)	Mini-DIN 4-pin (x1)
	Control	RS-232 (mini-din, 3-pin)
	USB	USB for remote
POWER	Voltage	100–240VAC, 50–60Hz (universal)
	Consumption	384 watts (typ)
CONTROLS	Physical	Standby, menu, input, reset, H/V keystone
	OnView®	Language (English, French, Spanish, German, Italian, Russian, Swedish, Finnish, Portuguese, Simplified Chinese and Traditional Chinese), brightness, contrast, frequency, phase, sharpness, zoom, keystone, V. position, H. position, color temperature, display format, audio(volume, treble, bass, stereo/mono, mute)
OPERATING CONDITIONS	Temperature	41–95°F (5–35°C)
	Humidity	10–85% (non-condensing)
NOISE LEVEL	Normal	33dB (typ)
	Whisper Mode	30dB (typ)
DIMENSIONS (WxHxD)	Physical	13.0" x 3.9" x 10.6" 330mm x 100mm x 269mm
WEIGHT	Net	7.5 lb. (3.4 kg)
	Gross	14.9 lb. (6.8 kg)
REGULATIONS		UL/C-UL, FCC B, TUV/GS, CB, CE B, CCC, VCCI
OTHER		Soft carrying case, remote with mouse control and laser pointer, picture-in-picture selectable display modes (PC/movie/game/sRGB/dynamic/user)
WARRANTY		Three-year limited warranty on parts and labor, first-year Express Exchange® Service. One-year warranty on lamp.**

specifications

Image Size (Diagonal in. wide - telephoto)	Height (in. wide - telephoto)	Width (in. wide - telephoto)	Throw Distance (in.)
30 – 25	18 – 15	24 – 20	47
74 – 62	44 – 37	59 – 49	118
123 – 103	74 – 62	98 – 82	197
172 – 144	103 – 86	138 – 115	276
197 – 164	118 – 98	158 – 131	315
241 – 205	148 – 123	197 – 164	394

Accuracy of the calculations are +/- 5%.
For additional calculations visit ViewSonic.com.

Optional Accessories

- ATA hard shipping case CASE-003
- Rolling soft case and laptop bag PRJ-SCA-001
- Replacement lamp RLC-002
- Universal ceiling mount kit WMK-005
- Extended Express Exchange® PRJ-EE-08-03



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.



ViewSonic

ViewSonic Corporation • 381 Brea Canyon Road, Walnut, CA 91789

Phone (800) 888-8583 or (909) 444-8888 • In Canada (866) 262-1967 • Fax (909) 839-7922 • SalesInfo@ViewSonic.com • ViewSonic.com

*Running whisper-mode exclusively can extend lamp life up to 4,000 hours. **Lamp warranty available in U.S. and Canada. Subject to terms and conditions, verification and approval. Third-year and 1-year limited lamp warranties apply only to current model projectors purchased after May 1, 2002. Applies to manufacturers installed lamp only. All accessory lamps purchased separately are warranted for 90 days. †Excluding major U.S. and Canadian holidays. †† Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs may vary by country. See your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2004 ViewSonic Corporation. All rights reserved [12173-00B-10/04] PJ755D-1

For more product information, visit us on the web at ViewSonic.com